

Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Features


1. RoHS compliant
2. Leaded type
3. Voltage rating: 140~500V_{ac}, 160~1000V_{dc}
4. Resistance range: 3.8 ~2000Ω
5. Stable over a long time
6. Operating temperature range:
-20 ~ +85°C (V=V_{max})
-40 ~ +125°C (V=0)
7. Agency recognition:
UL/cUL: File No. E138827
TUV: File No. R50426392 and R50499186
8. AEC-Q200 compliant products are available



■ Recommended Applications

1. Air conditioner
2. Server
3. LED lamp
4. Switch power supply

■ Part Number Code




Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Structure and Dimensions

● Structure



● Dimensions

(Unit: mm)

Part No.	D		T		H	d	P	L
	min	max	min	max	max	±0.02	±1.0	Min.
PPL123R8□A4A1	10.5	13.0	3.0	5.0	17.5	0.6	5	25
PPL09160□A2B2	8.5	11.0	3.0	5.0	14.5	0.6	5	25
PPL19100□A1B7	19.0	21.5	6.5	10.7	25.5	1.0	10	25
PPL16270□A2B7	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL16350□A2B7	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL16500□A2B7	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL16800□A2B7	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL19150□A2B7	19.0	21.5	6.5	10.7	25.5	1.0	10	25
PPL20400□A2B7	19.0	22.0	6.0	10.0	25.5	0.8	7.5	25
PPL20600□A2B7	19.0	22.0	6.5	10.7	25.5	1.0	10	25
PPL20330□A3B7	19.5	22.0	6.5	10.7	25.5	1.0	10	25
PPL20470□A3B7	19.5	22.0	6.5	10.7	25.5	0.8	7.5	25
PPL06121□A3B8	5.0	8.0	3.0	6.0	13.8	0.5	5	25
PPL11250□A2C8	10.5	13.0	4.0	6.5	17.0	0.6	5	25
PPL11500□A2C8	10.5	13.0	5.0	7.5	17.0	0.6	5	25
PPL11800□A2C8	10.5	13.0	5.0	7.5	17.0	0.6	5	25
PPL19500□A0C8	19.0	21.5	6.5	10.7	25.5	1.0	10	25
PPL11121□A2C8	10.5	13.0	5.0	7.5	17.0	0.6	5	25
PPL11151□A2C8	10.5	13.0	5.0	7.5	17.0	0.6	5	25
PPL16101□A2C8	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL11201□A2D2	10.5	13.0	5.0	7.5	17.0	0.6	5	25
PPL16151□A2D2	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL14121□A3D4	12.5	15.0	5.0	7.5	19.5	0.8	5	25
PPL14560□A3D4	12.5	15.0	5.0	7.5	19.5	0.8	5	25
PPL19102□A0D8	19.0	21.5	6.5	10.7	25.5	1.0	10	25
PPL16251□A2E0	15.5	18.0	5.0	7.5	21.5	1.0	10	25
PPL11501□A2E0	10.5	13.0	5.0	7.5	17.0	0.6	5	25


Note: For AEC-Q 200 qualified products, their d is 0.6mm for straight lead, and 0.8mm or 1.0mm for F lead. Please contact THINKING sales representatives and authorized distributors for detailed information.

Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Structure and Dimensions



● Dimensions

(Unit: mm)

Part No.	D		T		H	d	P	L
	min	max	min	max	max	±0.05	±1.0	Min.
PPL25601□A4G5	25	28	7	9.5	35	1.0	10	25
PPL25251□A2H5	25	28.5	7	9.5	35	1.0	10	25
PPL25102□A2J0	25	28.5	7.5	10.5	35	1.0	10	25
PPL25102□A4J0	25	28	7	9.5	35	1.0	10	25
PPL25301□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25501□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25801□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25102□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25132□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25152□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25182□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25202□A8J0	25	28.5	6	9.5	35	1.0	10	25
PPL25301□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25501□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25801□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25102□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25132□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25152□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25182□B2J0	25	28.5	6	9.5	35	1.0	10	25
PPL25202□B2J0	25	28.5	6	9.5	35	1.0	10	25

Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Characteristics

Part No.	Max. Voltage	Max. DC Link Voltage	Zero-power Resistance at 25°C	Curie Temperature	Max. Non-operating Energy at 60°C	Thermal Capacity	Safety Approvals	
	V _{max} (Vac)	V _{linkmax} (Vdc)	R ₂₅ (Ω)	T _c (°C)	E _{Non60} (J)	C _{th} (J/K)	UL/cUL	TUV
PPL123R8□A4A1	140	160	3.8	140	64	0.8	√	√
PPL09160□A2B2	220	310	16	120	24	0.4	√	√
PPL19100□A1B7	270	380	10	110	175	3.5	√	√
PPL19150□A2B7	270	380	15	120	210	3.5	√	√
PPL16270□A2B7	270	380	27	120	138	2.3	√	√
PPL20330□A3B7	270	380	33	130	266	3.8	√	√
PPL16350□A2B7	270	380	35	120	138	2.3	√	√
PPL20400□A2B7	270	380	40	120	192	3.2	√	√
PPL16500□A2B7	270	380	50	120	138	2.3	√	√
PPL20600□A2B7	270	380	60	120	228	3.8	√	√
PPL16800□A2B7	270	380	80	120	138	2.3	√	√
PPL20470□A3B7	280	400	47	130	266	3.8	√	√
PPL06121□A3B8	280	400	120	130	8	0.1	√	√
PPL11250□A2C8	380	540	25	115	55	1.0	√	√
PPL11500□A2C8	380	540	50	115	77	1.4	√	√
PPL19500□A0C8	380	540	50	100	140	3.5	√	√
PPL11800□A2C8	380	540	80	115	77	1.4	√	√
PPL16101□A2C8	380	540	100	120	138	2.3	√	√
PPL11121□A2C8	380	540	120	115	77	1.4	√	√
PPL11151□A2C8	380	540	150	115	77	1.4	√	√
PPL16151□A2D2	420	600	150	120	138	2.3	√	√
PPL11201□A2D2	420	600	200	120	84	1.4	√	√
PPL14560□A3D4	440	620	56	130	147	2.1	√	√
PPL14121□A3D4	440	620	120	130	147	2.1	√	√
PPL19102□A0D8	480	680	1000	100	152	3.8	√	√
PPL16251□A2E0	500	710	250	120	138	2.3	√	√
PPL11501□A2E0	500	710	500	115	77	1.4	√	√

Note 1: □ is the tolerance of R₂₅

Note 2: AEC-Q 200 qualified products of this series are available.

Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Characteristics

Part No.	Max. Voltage	Zero-power Resistance at 25°C	Curie Temperature	Thermal Capacity	Max. Non-operating Energy at 60°C	Safety Approvals	
	V _{max} (V _{dc})	R ₂₅ (Ω)	T _c (°C)	C _{th} (J/K)	E _{Non60} (J)	UL/cUL	TUV
PPL25601□A4G5	750	600	140	6.2	496	√	√
PPL25251□A2H5	850	250	120	6.2	372	√	√
PPL25102□A2J0	1000	1000	120	6.6	396	√	√
PPL25102□A4J0	1000	1000	140	6.2	496	√	√
PPL25301□A8J0	1000	300	185	6.2	775	–	–
PPL25501□A8J0	1000	500	185	6.2	775	–	–
PPL25801□A8J0	1000	800	185	6.2	775	–	–
PPL25102□A8J0	1000	1000	185	6.2	775	–	–
PPL25132□A8J0	1000	1300	185	6.2	775	–	–
PPL25152□A8J0	1000	1500	185	6.2	775	–	–
PPL25182□A8J0	1000	1800	185	6.2	775	–	–
PPL25202□A8J0	1000	2000	185	6.2	775	–	–
PPL25301□B2J0	1000	300	220	6.2	992	–	–
PPL25501□B2J0	1000	500	220	6.2	992	–	–
PPL25801□B2J0	1000	800	220	6.2	992	–	–
PPL25102□B2J0	1000	1000	220	6.2	992	–	–
PPL25132□B2J0	1000	1300	220	6.2	992	–	–
PPL25152□B2J0	1000	1500	220	6.2	992	–	–
PPL25182□B2J0	1000	1800	220	6.2	992	–	–
PPL25202□B2J0	1000	2000	220	6.2	992	–	–

Note 1: □ is the tolerance of R₂₅

Note 2: AEC-Q 200 qualified products of this series are available.

Note 3: PPL25301□A8J0, PPL25501□A8J0, PPL25801□A8J0, PPL25301□B2J0, PPL25501□B2J0, PPL25801□B2J0 are not applicable for short-circuit protection at 1000Vdc.

Ceramic PTC Thermistor: PPL Series


Dip Type for Inrush Current Limiter




Application and Selection

Typical application circuit


① DC circuit



② Three phases circuit



③ Single phase circuit



Selection

Calculation of the number of required PTC elements E_{Non60} : Max Non-operating Energy at 60°C ($T_a = 60$)

$$N \geq \frac{K * C * V^2}{2 * C_{th} * (T_c - T_a)}$$

$$E_{Non60} = (T_c - T_a) * C_{th}$$





K	K factor
	K = 1 for DC source
	K = 0.96 for 3-phase bridge rectifier
	K = 0.76 for single phase bridge rectifier
N	Number of required PTC thermistors connected in parallel
C	Capacitance of smoothing or DC link capacitor in F
V	Voltage of capacitor charging ($V = 1.414 * V_{ac}$) = $V_{link,max}$
C_{th}	Heat capacity in J/K
T_c	Curie temperature of PTC
T_a	Ambient temperature

Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



R-T Characteristic Curve (Typical)




Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Soldering Recommendation

● Wave Flow Soldering Profile



Note

- 1: $(1 \sim 3^\circ\text{C})/\text{sec}$
- 2: Approx. $200^\circ\text{C}/\text{sec}$
- 3: $5^\circ\text{C}/\text{sec}$. (Max)

● Recommended Reworking Conditions with Soldering Iron

Item	Conditions
Temperature of Soldering Iron-tip	360°C (max.)
Soldering Time	3 sec (max.)
Distance from Coating	2 mm (min.)

Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Reliability Test

Item	Standard	Test Conditions and Methods	Specifications															
Robustness of Terminations	IEC 60738-1	Gradually apply the specified force and keep the unit fixed for 10±1 sec. <table style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center; border-bottom: 1px solid black;">Terminal diameter (mm)</td> <td style="text-align: center; border-bottom: 1px solid black;">Force T(N)</td> </tr> <tr> <td style="text-align: center;">0.35<d≤0.5</td> <td style="text-align: center;">5.0</td> </tr> <tr> <td style="text-align: center;">0.5<d≤0.8</td> <td style="text-align: center;">10.0</td> </tr> <tr> <td style="text-align: center;">0.8<d≤1.25</td> <td style="text-align: center;">20.0</td> </tr> </table>	Terminal diameter (mm)	Force T(N)	0.35<d≤0.5	5.0	0.5<d≤0.8	10.0	0.8<d≤1.25	20.0	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage							
Terminal diameter (mm)	Force T(N)																	
0.35<d≤0.5	5.0																	
0.5<d≤0.8	10.0																	
0.8<d≤1.25	20.0																	
Solderability	IEC 60738-1	245±3°C, 2±0.5 sec	At least 95% of terminal electrode is covered by new solder															
Resistance to Soldering Heat	IEC 60738-1	260±3°C, 10±1 sec	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage															
Vibration	IEC 60738-1	Frequency range: 10~55Hz Amplitude: 0.75mm or acceleration: 98m/s ² Direction: 3 mutually perpendicular directions Duration: 6hrs (3x2 hrs)	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage															
Shock	IEC 60738-1	Wave: half-sine ΔV: 1.0m/s Acceleration: 50 m/s ² Pulse time: 30ms	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage															
Rapid Change of Temperature	IEC 60738-1	The thermal shock conditions shown below shall be repeated 5 cycles. <table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th>Step</th> <th>Temperature (°C)</th> <th>Period (minutes)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>-40 ± 3</td> <td>30 ± 3</td> </tr> <tr> <td>2</td> <td>Room temperature</td> <td>≤ 3</td> </tr> <tr> <td>3</td> <td>85 ± 2</td> <td>30 ± 3</td> </tr> <tr> <td>4</td> <td>Room temperature</td> <td>≤ 3</td> </tr> </tbody> </table>	Step	Temperature (°C)	Period (minutes)	1	-40 ± 3	30 ± 3	2	Room temperature	≤ 3	3	85 ± 2	30 ± 3	4	Room temperature	≤ 3	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage
Step	Temperature (°C)	Period (minutes)																
1	-40 ± 3	30 ± 3																
2	Room temperature	≤ 3																
3	85 ± 2	30 ± 3																
4	Room temperature	≤ 3																
Climatic Sequence	IEC 60738-1	Dry heat: 125°C for 16 hrs Damp heat first cycle: 40°C, 95% RH, cycle time: 24 hrs Cold: -40°C for 2 hrs Damp heat (cyclic), remaining cycles: 5 cycles Test according to IEC60068-2-30	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage															
Damp Heat, Steady State	IEC 60738-1	40±2°C, 90~95% RH, 1000±2hrs	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage															
Endurance at Maximum Operating Temperature and Maximum Voltage*1	IEC 60738-1	85± 2°C, V _{max} , 1000±2hrs	$ \Delta R_{25}/R_{25} \leq 20\%$ No visible damage															
Endurance Test for Charging of Capacitor	Specification Standard	Operating cycles at V _{max} , 100,000 cycles (charging of capacitor)	$ \Delta R_{25}/R_{25} < 25\%$ No visible damage															

Note: *1 Items are not applicable for PPL25□A8J0, PPL25□B2J0


Ceramic PTC Thermistor: PPL Series

Dip Type for Inrush Current Limiter



■ Packaging

● Taping Specification



● Parameter List

(Unit: mm)

Index	Parameter	Nominal dimensions		Tolerance
P	Lead spacing	5		±1
P ₀	Sprocket hole pitch	12.7	15	±0.3
P ₁	Ordinate to adjacent component lead	3.85	5	±1
P ₂	Device pitch	12.7 (D ≤ 10) 25.4 (D > 10)	15.0 (D ≤ 10) 30.0 (D > 10)	±1
H ₀	Abscissa to plane (kinked lead)	16	16	±0.5
H ₁	Abscissa to top	33.5(D=11) 36.0(D=14)		Max.
W	Carrier tape width	18	18	±1
W ₀	Hold-down tape width	12	12	±1.5
W ₁	Sprocket hole position	9	9	±1
W ₂	Top distance between tape edges	3	3	Max.
ΔP	Body tape plane deviation	1	1	Max.
Δh	Body lateral deviation	2	2	Max.
D ₀	Sprocket hole diameter	4	4	±0.2
t	Tape thickness	0.6	0.6	±0.2

Note: D is the PTC disc diameter.

Ceramic PTC Thermistor: PPL Series


Dip Type for Inrush Current Limiter



Quantity

Bulk Packing

Disc Size (mm)	Quantity (pcs/bag)
$06 \leq \Phi \leq 10$	200
$11 \leq \Phi \leq 16$	100
$19 \leq \Phi \leq 20$	50
$\Phi = 25$	30



Reel Packing


Disc Size (mm)	Quantity (pcs/reel)
$\Phi = 06$	1,500
$\Phi = 11$	500
$\Phi = 12$	750
$\Phi = 14$	500
$\Phi \geq 16$	500 ($V_r \leq 270V$) 250 ($V_r > 270V$)

Disc Size	$\Phi < 16$	$\Phi \geq 16$
A	46	55

(Unit: mm)

Ammo Packing

Disc Size (mm)	Quantity (pcs/box)
$\Phi = 06$	1,500
$\Phi = 11$	750
$\Phi = 12$	1,000
$\Phi = 14$	500
$\Phi \geq 16$	500



Warehouse Storage Conditions of Products

Storage Conditions

1. Storage Temperature: $-10^{\circ}C \sim +40^{\circ}C$
2. Relative Humidity: $\leq 75\%RH$
3. Keep away from corrosive atmosphere and sunlight.

Period of Storage 1 year

Usage

Please keep products away from the conditions mentioned below to avoid their characteristic deterioration and failure.

1. Corrosive gas or deoxidizing gas (Cl_2 , H_2S , NH_3 , SO_x , NO_x etc.)
2. Place in a vacuum or put pressure
3. Salt water, oil, solvent and chemical liquid
4. Flammable gas
5. Place in splashed water, or high humidity and dewing place
6. Other places similar to any conditions mentioned above